

MATERIAL SAFETY DATA SHEET

HMIS CODES:

H	F	R	P
0	2	0	A

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administrator
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

IDENTITY (AS USED ON LABEL AND LIST):

JOMAR GIMME the WHITE STUFF

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name:

JOMAR INTERNATIONAL INC.

Emergency Telephone Number:

(586) 268-1220

Address (Number, Street, City, State, and ZIP Code):

7243 MILLER DRIVE

Telephone Number for Information:

(586) 268-1220

SUITE 100

Date Prepared: January 18, 2005

WARREN, MI 48092

Signature of Preparer (optional):

Section II - Hazardous Ingredients/Identity Information

HAZARDOUS COMPONENTS

(SPECIFIC CHEMICAL IDENTITY: COMMON NAME(S))

OSHA
PEL

ACGIH
TLV

OTHER LIMITS
Recommended

%
(optional)

ISOPROPANOL [CAS#67-63-0]

400 ppm

400 ppm

N/A

8 - 13%

BUTYL CELLOSOLVE [CAS#111-76-2]

50 ppm

25 ppm

N/A

20 - 25%

Section III - Physical/Chemical Characteristics

Boiling Point:

180°F

Specific Gravity (H₂O = 1):

1.41

Vapor Pressure (mm Hg):

.88

Melting Point:

N/A

Vapor Density (AIR = 1):

> 1

Evaporation Rate (Butyl Acetate = 1):

0.6

Solubility in Water: SLIGHT

Appearance and Odor: WHITE PASTE - MILD ODOR

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used):

82°F (28°C) ASTM METHOD D93-80

Flammable Limits:

921°F (494°C) IGNITION TEMPERATURE

LEL:

1.1%

UEL:

10.6%

Extinguishing Media: CARBON DIOXIDE OR DRY CHEMICAL OR WATER.

Special Fire Fighting Procedures: NONE

Unusual Fire and Explosion Hazards:

CONTACT WITH STRONG OXIDIZERS MAY CAUSE FIRES OR EXPLOSIONS. CARBON MONOXIDE MAY BE RELEASED.

Section V - Reactivity Data		JOMAR GIMME the WHITE STUFF	
Stability:	Unstable:		Conditions to Avoid: N/A
	Stable:	X	
Incompatibility (Materials to Avoid): LIQUID OXYGEN SYSTEMS, LIQUID SODIUM, GASEOUS FLUORINE, STRONG OXIDIZERS.			
Hazardous Decomposition or Byproducts: N/A			
Hazardous Polymerization:	May Occur:		Conditions to Avoid: N/A
	Will Not Occur:	X	
Section VI - Health Hazard Data			
Route(s) of Entry:	Inhalation? YES	Skin? YES	Ingestion? YES
Health Hazards (Acute and Chronic): NONE			
Carcinogenicity:	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO
Signs and Symptoms of Exposure: INHALATION: POSSIBLE DIZZINESS IF USED IN CONFINED AREA. SKIN: MAY CAUSE MILD IRRITATION TO SENSITIVE SKIN.			
Medical Conditions Generally Aggravated by Exposure: NONE KNOWN.			
Emergency and First Aid Procedures: EYE CONTACT: FLUSH EYES WITH WATER. SKIN: WASH EXPOSED AREA WITH SOAP AND WATER. WASH CLOTHING BEFORE REUSE. INHALATION: MOVE TO WELL VENTILATED AREA. INGESTION: CONSULT A PHYSICIAN.			
Section VII - Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled: NORMAL GOOD HOUSEKEEPING PROCEDURES.			
Waste Disposal Method: DISPOSAL TO BE DONE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.			
Precautions to Be Taken in Handling and Storing: STORE AWAY FROM HEAT OR OPEN FLAME. CLOSE CONTAINER AFTER USE.			
Other Precautions: WEAR PROTECTIVE GLOVES TO PREVENT POSSIBLE SKIN ABSORPTION AND DERMATITIS. KEEP OUT OF REACH OF CHILDREN.			
Section VIII - Control Measures			
Respiratory Protection (Specify Type): AVOID BREATHING OF FUMES. IF USED IN A CONFINED AREA, A RESPIRATOR MAY BE NECESSARY.			
Ventilation:	Local Exhaust: NORMAL VENTILATION IS ADEQUATE.		Special: N/A
	Mechanical (General): N/A		Other: N/A
Protective Gloves: MAY BE NECESSARY FOR SENSITIVE SKIN.		Eye Protection: KEEP OUT OF EYES. WEAR PROTECTIVE GOGGLES WHERE NECESSARY.	
Other Protective Clothing or Equipment: N/A			
Work/Hygienic Practices: WASH UP WITH SOAP AND WATER AFTER USE.			