

SAFETY DATA SHEET.

Issuing date 07-Jan-2015 Revision Date 07-Jan-2015 Version 2.07

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 80-699 FOUR WAY LUBE WITH PTFE

Recommended use of the chemical

and restrictions on use

Product code F00518

<u>Product Type</u> Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use Penetrating lubricant with PTFE.

Uses advised against

Manufactured For: Kimball Midwest 4800 Roberts Rd. Columbus, OH 43228

Emergency telephone number

Chemical Emergency Phone Chemtrec 1-800-424-9300

Number

Company Emergency Phone 800-233-1294

Number

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation

May cause drowsiness or dizziness

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Slightly Hazy

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash hands thoroughly after handling

Wear protective gloves

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Keep container tightly closed.

Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

· Toxic to aquatic life with long lasting effects

0.00000938 %% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
HYDROTREATED LIGHT DISTILLATES	64742-47-8	35-45
NAPHTHENIC OIL, SEVERELY HYDROT	64742-52-5	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
KEROSENE	8008-20-6	1-10

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, and clothing. Avoid breathing, vapors, mist, or gas.

Eye contact Rinse immediately with plenty of water and seek medical advice.

Skin contact Wash off immediately with plenty of water. Remove and wash contaminated clothing before

re-use. Get medical attention immediately if symptoms occur.

Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms May cause skin irritation. Inhalation causing Central Nervous System effects. ingestion

causing lung damage.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable or extremely flammable aerosol. Container may burst in fire.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use with adequate ventiliation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Contain liquid and collect with an inter,non-combustible material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventiliation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such

as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible products Store away from strong oxidizers and acids.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Expecure Gardonnes			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m³

KEROSENE	TWA: 200 mg/m³ total	-	TWA: 100 mg/m ³
8008-20-6	hydrocarbon vapor application		
	restricted to conditions in which		
	there are negligible aerosol		
	exposures		
	Skin - potential significant		
	contribution to overall exposure		
	by the cutaneous route		ļ

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Exposure controls

Engineering MeasuresVentilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Based on propellant

Not applicable

provided in accordance with current local regulations.

Hygiene measuresHandle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol

Appearance Slightly Hazy Odor Solvent

ColorOdor ThresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Methods</u>

PH No information available

Melting/freezing point No information available

Palling point/builing range

No information available

Boiling point/boiling rangeNo information available
Flash Point

No information available
-96.4 °C / -141 °F

Evaporation rateFlammability (solid, gas)
No information available
No information available

Flammability Limits in Air

upper flammability limitNo information availablelower flammability limitNo information available

Vapor pressure
Vapor density

No information available
No information available
No information available

Specific Gravity 0.805

Water solubility Practically insoluble Partition coefficient: n-octanol/waterNo information available

Autoignition temperature

Decomposition temperature

No information available
No information available
No information available

ViscosityNo information availableExplosive propertiesNo information available

Other information

VOC Content(%) 24.12

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Store away from strong oxidizers and acids.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known information

Inhalation Exposure to high vapour concentrations may cause nervous systems effects such as

headache, nausea, and dizziness.

Eye contact May cause slight irritation.

Skin contact Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.

Ingestion Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung

damage which may be fatal.

Component Information

Compension information			
Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
KEROSENE 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting .

Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Contact with eyes may cause irritation. Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal. May cause mild irritation. Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Not acutely toxic. Aspiration into the

lungs during swallowing may cause serious lung damage which may be fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ Cell Mutagenicity No information available.

Carcinogenicity There are no known carcinogenic chemicals in this product.

Reproductive toxicityThe ingredients are not reproductive hazards.

Revision Date 07-Jan-2015

Specific target organ systemic toxicity (single exposure)
Specific target organ systemic toxicity (repeated exposure)

May cause drowsiness and dizziness.

No information available.

Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis.

Central nervous system, Eyes, Respiratory system, Skin.

Target Organ Effects
Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.00000938 %% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 10656 mg/kg ATEmix (dermal) 4262 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through	-	-
NAPHTHENIC OIL, SEVERELY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	 -	-	<u>-</u>	-

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

Revision Date 07-Jan-2015

DOT Ground CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HYDROTREATED LIGHT DISTILLATES	Х	Х	X	Х	Х	Х	Х	Х
NAPHTHENIC OIL, SEVERELY HYDROT	Х	Х	Х	Х	Х	Х	Х	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
KEROSENE	Х	Х	Х	Х	X	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardYesFire HazardYesSudden Release of Pressure HazardYesReactive Hazardno

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

No warning required.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE	X	X	X
8008-20-6			

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2 Flammability 4 Physical Hazard 1 Personal protection B

Prepared ByRegulatory AffairsIssuing date07-Jan-2015Revision Date07-Jan-2015

Revision Note

(M)SDS sections updated

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet