
SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: AcrylPro® Tile Adhesive

Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Ceramic Tile Adhesive

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address: Custom Building Products
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305

Telephone Number: (562)-598-8808

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR

1910.1200 (OSHA HAZCOM2012)

Carcinogenicity
STOT-RE

Category 1A
Category 2

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:
DANGER!

2.2b HAZARD STATEMENTS
May cause cancer
Causes damage to organs through prolonged or repeated exposure

2.2c HAZARD PICTOGRAMS



SAFETY DATA SHEET

2.2d PRECAUTIONARY STATEMENTS

| | |
|----------------------|--|
| i. PREVENTION | Wash hands thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. |
| ii. RESPONSE | If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: call a poison center/doctor. If exposed or concerned: get medical advice/attention. |
| iii. STORAGE | Store locked up. Store in a well-ventilated place. Keep container tightly closed. |
| iv. DISPOSAL | Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations. |

2.3 ADDITIONAL INFORMATION

2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED

Not applicable

2.3b UNKNOWN ACUTE TOXICITY

4.5% of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

| Chemical Name | CAS Number | Weight % |
|----------------------------|-------------------------|-----------|
| Calcium Carbonate | 1317-65-3 | 30 – 60%* |
| Ethylene Glycol | 107-21-1 | 1 – 5%* |
| Petroleum Distillates | 64742-88-7 / 64742-47-8 | 0.1 – 1%* |
| Crystalline Silica, Quartz | 14808-60-7 | 0.1 – 1%* |

*Means that the component will fall into one the ranges specified due to batch-to-batch variability.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

SAFETY DATA SHEET

| ROUTES OF EXPOSURE | DESCRIPTION |
|----------------------|--|
| Eye Contact: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately. |
| Skin Contact: | In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. |
| Inhalation: | If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |
| Ingestion: | If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention. |

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

| ROUTES OF EXPOSURE | DESCRIPTION |
|----------------------|--|
| Eye Contact: | May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Skin Contact: | May cause skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. |
| Inhalation: | May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease. |
| Ingestion: | May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting. |

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Not applicable

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Not Flammable by WHMIS/OSHA HAZCOM2012 Criteria

5.2 EXTINGUISHING MEDIA

5.2a. Suitable Extinguishing Media:

SAFETY DATA SHEET

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

5.2b. Unsuitable Extinguishing Media:

CAUTION: Use of water spray when fighting fire may be inefficient

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

5.3a. Products of Combustion:

May include, and are not limited to: oxides of carbon

5.3b. Explosion Data

i. Sensitivity to Mechanical Impact:

Not available.

ii. Sensitivity to Static Discharge:

Not available.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment: Prevent further leakage or spillage if safe to do so. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Pick up and transfer to properly labeled containers

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Use in well-ventilated areas. Wear chemical resistant gloves and eye protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not take internally.

General Hygiene Advice: Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.

SAFETY DATA SHEET

Store locked up. Store at room temperature and keep containers closed when not in use.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETER Exposure Guidelines

| Occupational Exposure Limits | | |
|------------------------------|---|-----------------------------|
| Chemical Name | OSHA-PEL | ACGIH-TLV |
| Calcium Carbonate | 5 mg/m ³ (Resp.) 15 mg/m ³ (Total) | 5 mg/m ³ (Resp.) |
| Ethylene Glycol | 50 ppm | 50 ppm |
| Petroleum Distillates | 200 mg/m ³ | 200 mg/m ³ |
| Crystalline Silica, Quartz | 0.1 mg/m ³ | 0.025 mg/m ³ |

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES

8.3a. Personal Protective Equipment:

- i. **Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]
- ii. **Skin Protection:**
 1. **Hand Protection:** Wear chemical resistant gloves.
 2. **Body Protection:** Wear suitable protective clothing
- iii. **Respiratory Protection:** A NIOSH approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. **General Health and Safety Measures:** Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---------------|
| Appearance (physical state, color, etc.): | White Paste |
| Odor: | Latex |
| Odor Threshold: | Not available |

SAFETY DATA SHEET

| | |
|---|------------------|
| pH: | 8.50 – 9.30 |
| Melting point/Freezing point: | Not available |
| Initial boiling point and boiling range: | Not available |
| Flash point: | Not available |
| Evaporation rate (Water=1): | Not available |
| Flammability: | Not flammable |
| Upper Flammability/Explosive Limit: | Not available |
| Lower Flammability/Explosive Limit: | Not available |
| Vapor Pressure | Not available |
| Vapor Density: | Not available |
| Relative Density: | 1.20 – 1.35 g/mL |
| Solubility in Water: | Slightly Soluble |
| Partition coefficient: n-octanol/water: | Not available |
| Auto-ignition temperature: | Not available |
| Decomposition Temperature: | Not available |
| Viscosity (cps): | Not available |
| VOC Content: | 65 g/L |

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under recommended storage conditions

10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

10.5. INCOMPATIBLE MATERIALS

Strong acids and oxidizing agents.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

Eye Contact: May cause eye irritation. Symptoms may include discomfort or pain,

SAFETY DATA SHEET

excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin Contact: May cause skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis.

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

| Acute Toxicity | | |
|-----------------------------------|----------------------------|--------------------------|
| Total ATE mix (oral) = 8073 mg/kg | | |
| Chemical Name | LC50 | LD50 |
| Calcium Carbonate | Not available | Oral: > 5,000 mg/kg, rat |
| Ethylene Glycol | Inhalation: >2.5 mg/L, rat | Oral: 4,700 mg/kg, rat |
| Petroleum Distillates | Inhalation: > 5000ppm, rat | Oral: > 5,000 mg/kg, rat |
| Crystalline Silica, Quartz | Not available | Not available |

| Carcinogenicity | |
|----------------------------|---|
| Chemical Name | Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65) |
| Calcium Carbonate | Not Listed |
| Ethylene Glycol | G-A4 |
| Petroleum Distillates | Not Listed |
| Crystalline Silica, Quartz | N-A2, I-1, O-1, ACGIH-A2, CP65 |

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

| SHORT-TERM | |
|--|--|
| Skin Corrosion/Irritation: | May cause skin irritation |
| Serious Eye Damage/Irritation: | May cause eye irritation |
| Respiratory Sensitization: | Not available |
| Skin Sensitization: | Not available |
| STOT-Single Exposure: | Not available |
| Aspiration Hazard: | Not available |
| LONG-TERM | |
| Carcinogenicity: | May cause cancer |
| Germ Cell Mutagenicity: | Not available |
| Reproductive Toxicity: | Not available |
| STOT-Repeated Exposure: | Causes damage to organs through prolonged or repeated exposure |
| Synergistic/Antagonistic Effects: | Not available |

SAFETY DATA SHEET

Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

May cause long-term, adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

| Ecotoxicity | | |
|----------------------------|--------------------|--------------------|
| Chemical Name | EC50/NOEC-48 Hours | LC50/NOEC-96 Hours |
| Calcium Carbonate | Not available | Not available |
| Ethylene Glycol | Not available | Not available |
| Petroleum Distillates | Not available | Not available |
| Crystalline Silica, Quartz | Not available | Not available |

12.2. PERSISTENCE AND DEGRADABILITY

Not available

12.3. BIOACCUMULATIVE POTENTIAL

Not available

12.4. MOBILITY IN SOIL

Not available

12.5. OTHER ADVERSE EFFECTS

Not available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

13.2. OTHER DISPOSAL CONSIDERATIONS

Not available

Section 14: TRANSPORT INFORMATION

| DOT (U.S.) | TDG (CANADA) |
|---|---|
| UN NUMBER: Not regulated | UN NUMBER: Not regulated |
| UN PROPER SHIPPING NAME: Not regulated | UN PROPER SHIPPING NAME: Not regulated |
| TRANSPORT HAZARD CLASS (ES): | TRANSPORT HAZARD CLASS (ES): |

Conforms to OSHA HazCom 2012 Standard and WHMIS

SAFETY DATA SHEET

| | |
|---------------------------------------|---------------------------------------|
| Not regulated | Not regulated |
| PACKING GROUP (if applicable): | PACKING GROUP (if applicable): |
| Not regulated | Not regulated |

SUMMARY: Product is not regulated under DOT/TDG and other transportation regulations.

14.1. ENVIRONMENTAL HAZARDS

Not available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available

14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

US: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

| CHEMICAL NAME | SARA TITLE III | | | |
|----------------------------|--------------------------------|-----------------------------|--------------------|----------------------|
| | SECTION 302 (EHS) TPQ (LBS) | SECTION 304 EHS RQ (LBS) | CERCLA RQ (LBS) | SECTION 313 (TRI) |
| Calcium Carbonate | Not Listed | Not Listed | Not Listed | Not Listed |
| Ethylene Glycol | Not Listed | Not Listed | 5,000 | 313 |
| Petroleum Distillates | Not Listed | Not Listed | Not Listed | Not Listed |
| Crystalline Silica, Quartz | Not Listed | Not Listed | Not Listed | Not Listed |

15.3. US STATE RIGHT TO KNOW LAWS:

| | |
|---|---|
| California Proposition 65: | WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm |
| Other U.S. States "Right to Know" Lists: | |
| New Jersey: | Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Petroleum Distillate: CAS#64742-88-7 Petroleum Distillate: CAS#64742-47-8 |

Conforms to OSHA HazCom 2012 Standard and WHMIS

SAFETY DATA SHEET

| | |
|-----------------------|---|
| Pennsylvania: | Silica, Quartz: CAS#14808-60-7 Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Petroleum Distillate: CAS#64742-88-7 Petroleum Distillate: CAS#64742-47-8 Silica, Quartz: CAS#14808-60-7 |
| Massachusetts: | Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Petroleum Distillate: CAS#64742-88-7 Petroleum Distillate: CAS#64742-47-8 Silica, Quartz: CAS#14808-60-7 |
| Minnesota: | Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Petroleum Distillate: CAS#64742-88-7 Petroleum Distillate: CAS#64742-47-8 Silica, Quartz: CAS#14808-60-7 |
| Florida: | Not Available |
| Michigan: | Not Available |

15.4. GLOBAL INVENTORIES

| Chemical Name | USA TSCA | Canada DSL/NDSL |
|----------------------------|----------|-----------------|
| Calcium Carbonate | Yes | NDSL(*) |
| Ethylene Glycol | Yes | DSL |
| Petroleum Distillates | Yes | DSL |
| Crystalline Silica, Quartz | Yes | DSL |


*Exemption: Natural occurring chemical

Conforms to OSHA HazCom 2012 Standard and WHMIS

SAFETY DATA SHEET

15.5. NFPA AND HMIS RATINGS:

| | |
|---|--|
| <p>HEALTH HAZARD</p> <p>4 EXTREME - High, toxic - May be fatal on short-term exposure.</p> <p>3 SERIOUS - Toxic. Eye irritation and breathing apparatus should be worn.</p> <p>2 MODERATE - Eye irritation, respiratory and face mask should be worn.</p> <p>1 SLIGHT - Breathing apparatus may be worn.</p> <p>0 MINIMAL - No precautions necessary.</p> | <p>FLAMMABILITY HAZARD</p> <p>4 EXTREME - Extremely flammable gas or liquid. Flash Point below 100°F.</p> <p>3 SERIOUS - Flammable. Flash Point 100°F to 200°F.</p> <p>2 MODERATE - Combustible. Flash Point between 200°F to 300°F.</p> <p>1 SLIGHT - Slightly combustible. Flash Point above 300°F.</p> <p>0 MINIMAL - Will not burn under any conditions.</p> |
| <p>SPECIFIC HAZARD</p> <p>OXIDIZER OXY</p> <p>ACID ACID</p> <p>ALKALI ALK</p> <p>CORROSIVE COR</p> <p>Use NO WATER W</p> <p>RADIATION ☼</p> | <p>INSTABILITY HAZARD</p> <p>4 EXTREME - Explosive at room temperature.</p> <p>3 SERIOUS - May detonate if shocked or heated under confinement or mixed with water.</p> <p>2 MODERATE - Unstable. May react with water.</p> <p>1 SLIGHT - May react if heated or mixed with water.</p> <p>0 MINIMAL - Normally stable. Does not react with water.</p> |



HMIS

| Hazard Index | |
|--------------|-----------------|
| 4 | Severe Hazard |
| 3 | Serious Hazard |
| 2 | Moderate Hazard |
| 1 | Slight Hazard |

| | | |
|------------------------------|--|---|
| 2 HEALTH | PROTECTIVE EQUIPMENT INDEX | |
| 0 FLAMMABILITY | A | G |
| 0 REACTIVITY | B | H |
| 0 PERSONAL PROTECTION | C | I |
| B | D | J |
| | E | K |
| | F | X |
| | Ask your supervisor for special handling instructions. | |

15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

| | |
|------------------|--|
| CP65 | California Proposition 65 |
| OSHA (O) | Occupational Safety and Health Administration |
| ACGIH (G) | American Conference of Governmental Industrial Hygienists <ul style="list-style-type: none"> • A1 – Confirmed human carcinogen • A2 – Suspected human carcinogen • A3 – Animal carcinogen • A4 – Not classifiable as a human carcinogen • A5 – Not suspected a human carcinogen |
| IARC (I) | International Agency for Research on Cancer <ul style="list-style-type: none"> • 1 – The agent (mixture) is carcinogenic to humans |

Conforms to OSHA HazCom 2012 Standard and WHMIS

SAFETY DATA SHEET

| | |
|----------------|---|
| | <ul style="list-style-type: none"> • 2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. • 2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals. • 3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. • 4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans. |
| NTP (N) | National Toxicology Program <ul style="list-style-type: none"> • 1 – Known to be carcinogens • 2 – Reasonably anticipated to be carcinogens |

Section 16: OTHER INFORMATION

Date of Preparation: September 16, 2014

Version: 2.0

Revision Date: June 17, 2016

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by: Custom Building Products
Phone: (562)-968-2980
www.custombuildingproducts.com

End of Safety Data Sheet